

SONY[®]

EIA/CCIR

Black and White Video Monitor

PVM-4B1U/4B1E




An assembly of four 4-inch monochrome monitors for multiple monitor viewing

Features

- Ideal for camera monitoring in video studio and surveillance systems with multiple camera installations
- Compatible with EIA and CCIR systems (automatically selected)
- High resolution of 500TV lines
- Stable picture reproduction with the high voltage regulation circuit
- Accepts an external sync signal
- Loop-through video and sync terminals with automatic 75Ω termination
- Can be mounted in a standard 19-inch rack
- Individual power and individual controls available



Front view



Rear view

Specifications



General

System: EIA 525 lines/60 fields,
 CCIR 625 lines/50 fields (automatically selected)
 Frequency response: 10MHz (-3dB)
 Power requirements: AC 100 to 240V*, 50/60Hz
 Power consumption: 59W
 Mass: 11.7kg (25lb 13oz)
 Operating temperature: 0 to 35°C (32 to 95°F)
 Operating humidity: 0 to 90%

CRT performance

CRT type: 10cm (4-inch) CRT,
 visible picture size 9.4cm
 (3 3/4inch) (min.) measured
 diagonally, 50° deflection
 Resolution: 500TV lines

Dimensions



Unit: mm (inch)

Picture performance

Normal scan: 7% overscan
 Linearity: H: less than 8%, V: less than 7%

Input performance

VIDEO: Loop-through BNC
 1Vp-p±6dB, sync negative,
 automatic 75Ω termination
 EXT SYNC: Loop-through BNC
 0.5 to 4Vp-p, sync negative,
 automatic 75Ω termination

Safety regulations

PVM-4B1U: UL1950, CSA950, DHHS, DNHW
 FCC Class A, IC Class A
 PVM-4B1E: CE, LVD (TÜV)

Supplied accessories

AC power cord (1)
 AC plug holder (1set)
 Operating instructions (1)

*UL listed for 120V operation.

Distributed by

Features and specifications subject to change without notice.